




[IPN Home](#) | [Search](#) | [Order](#) | [Shopping Cart](#) | [Login](#) | [Site Map](#) | [Help](#)



JP9131305A2: FLUORESCENCE OBSERVATION ENDOSCOPE

[View Images \(1 pages\)](#) | [View INPADOC only](#)

Country: **JP** Japan
Kind:
Inventor(s): **UTSUI TETSUYA**
ADACHI RIYUUSUKE
UEDA HIROHISA
SANO HIROSHI
Applicant(s): **ASAHI OPTICAL CO LTD**
News, Profiles, Stocks and More about this company
Issued/Filed **May 20, 1997 / Nov. 9, 1995**
Dates:
Application **JP1995000290854**
Number:
IPC Class: **A61B 1/04; A61B 1/00;**

Abstract: **Problem to be solved:** To provide a fluorescence observation endoscope allowing the optimum fluorescence observation by setting a prescribed difference between the longest wavelength of the light permeating an excitation light filter and shortest wavelength of the light permeating a fluorescence observation filter, and forming both filters having the transmission factor of a specific value or above.
Solution: An excitation light filter 12 is arranged in the illumination light path between a light source lamp 11 and an object, and a fluorescence observation filter 45 is arranged in the observation light path between the object and an observation section for observing the image of the object in this fluorescence observation endoscope. A difference 20-40nm is set between the longest wavelength in the wavelength region of the excitation light filter 12 having the transmission factor 10% or above and the shortest wavelength in the wavelength region of the fluorescence observation filter 45 having the transmission factor 10% or above. The longest wavelength in the wavelength region of the excitation light filter 12 having the transmission factor 10% or above is preferably set to 455-460nm, and the shortest wavelength in the wavelength region of the fluorescence observation filter 45 having the transmission factor 10% or above is preferably set to 480-495nm.

COPYRIGHT: (C)1997,JPO

BEST AVAILABLE COPY